

BOOST YOUR BOTTOM LINE

The ZT7000 is the peak of toughness and best-inthe-business performance. With transport speeds up to 19 MPH and mowing speeds up to 13 MPH, you can knock out quality results, job after job.



MODEL NUMBER	72" - 0007011	
	72" = 9997011	
ENGINE	V - EV4000V	
Model	Kaw FX1000V	
Displacement	60.9 cu. in. (999 cc)	
Fuel Capacity	15.0 gal. (56.7 L)	
Air Filter	Canister Air Filter	
ELECTRICAL		
Charging System	15 amp	
Clutch	250 lbf. (1112 N)	
DECK		
Mower Deck	AirFX™ Cutting System	
Leading Edge	Adjustable, Front Lip Standard	
Width	72.0 (1828 mm)	
Adjustable Anti-Scalp Rollers	7	
Cutting Height	1.0-5.5 in. (25-139 mm)	
Blade Tip Speed	18,152 fpm @ 3550 Engine rpm	
Discharge Chute	Flexible Molded Polymer	
FRAME		
Front & Rear	Welded, 0.25 in., 7-gauge Steel; 1.5 x 2.5 in. Steel Tubing	
Machine Length	87.0 in. (2209 mm)	
Machine Weight	1541 wet lb.	
TRANSMISSION		
Туре	HG ZT-5400 2-Speed Hydrostatic Transaxles	
Pump Displacement	0.9 cu. in. (16 cc)	
Oil Capacity	1.4 gal. (5.9 qt.) each	
Forward Speed	0-19.0 mph (0-30.5 km/hr.)*	
Reverse Speed (mph)	0-7.5 mph (0-12.0 km/hr.)**	
WHEELS		
Drive Wheel Size	26 x 12.0-12	
Front Caster Wheel Size	15 x 6.5-6, No-Flat	
Caster Arm Attachment	Bolt-On	
SEAT		
Description	Extra-High Back, Full Mechanical Suspension Seat	
Fore-Aft Adjustment	Seat Slide Lever	
		* 0_13 mnh cutting: 13_10 mnh transport

* 0–13 mph cutting; 13–19 mph transport ** 5–7.5 mph transport





Everything we put into Bobcat equipment is designed to make more of whatever you bring to the job. Whether it's strength, versatility, speed or agility, it's built around you.

Certain specification(s) are based on engineering calculations and are not actual measurements. Specification(s) are provided for comparison purposes only and are subject to change without notice. Specification(s) for your individual Bobcat equipment will vary based on normal variations in design, manufacturing, operating conditions, and other factors. Where applicable, dimensions are in accordance with ISO standards. Specifications and design are subject to change without notice. Pictures of Bobcat units may show other than standard equipment. All dimensions are given for mini track loaders. All dimensions are shown in inches. Respective metric dimensions are enclosed by parentheses. Bobcat Company complies with the requirements of ISO 9001 as registered with BSI.

Bobcat®, the Bobcat logo and the colors of the Bobcat machine are registered trademarks of Bobcat Company in the United States and various other countries. ©2021 Bobcat Company. All rights reserved.



