

ZT2000



Bobcat®

One Tough Animal.

**MY HOUSE IS WHERE I SLEEP,
MY YARD
IS WHERE
I LIVE.**

BRING TOUGH TO TURF

PROFESSIONAL CUT AFFORDABLE PRICE

With the ZT2000 you get more commercial features than any other zero-turn mower in the same price range. It's the ZT for anyone who wants durability and a professional cut at an affordable price.



ZT2000

MODEL NUMBER	42" = 9992001	48" = 9992002	52" = 9992003
ENGINE			
Model	Kaw FR651V	Kaw FR651V	Kaw FR691V
Displacement		44.3 cu.ci. (726 cc)	
Fuel Capacity		3.8 gal. (14.3 L)	
Air Filter		Dual Element	
ELECTRICAL			
Charging System		15 amp	
Clutch		105 lb. (556 N)	
DECK			
Mower Deck	TufDeck™ 7-gauge Top; 7-gauge side skirts	TufDeck™ 10-gauge Top with 7-gauge Spindle Supports; 7-gauge Side Skirts	
Width	42.0 in. (1066 mm)	48.0 (1219 mm)	52.0 (1320 mm)
Adjustable Anti-Scalp Rollers	2	3	3
Cutting Height		1.5-4.8 in. (38-121 mm)	
Blade Tip Speed	18,809 fpm @ 3550 Engine rpm	17,365 fpm @ 3550 Engine rpm	18,142 fpm @ 3550 Engine rpm
Discharge Chute		Flexible Molded Polymer	
FRAME			
Front & Rear	Welded 7-gauge Steel; 1.5- x 2.5-inch Steel Tubing		
Machine Length		76.0 in. (1930 mm)	
Machine Weight	684 wet lb.	736 wet lb.	752 wet lb.
TRANSMISSION			
Type	HG ZT-2800 Hydrostatic Transaxles		
Pump Displacement	0.6 cu. in. (10 cc)		
Oil Capacity	1.0 gal. (4 qt)		
Forward Speed	0-7.0 mph (0-11.2 km/hr.)		
Reverse Speed (mph)	0-3.0 mph (0-4.8 km/hr.)		
WHEELS			
Drive Wheel Size	20 x 8.0-10	20 x 10.0-10	
Front Caster Wheel Size	11 x 6.0-5		
Caster Arm Attachment	Welded to Frame		
SEAT			
Description	High-Back, Spring Suspension Seat		
Fore-Aft Adjustment	Seat Slide Lever		

**500
HOURS**

BUMPER TO BUMPER

WARRANTY

BOBCAT.COM



YOU ARE ONE TOUGH ANIMAL.®

Everything we put into Bobcat equipment is designed to make more of whatever you bring to the job. Whether it's strength, versatility, speed or agility, it's built around you.

Certain specification(s) are based on engineering calculations and are not actual measurements. Specification(s) are provided for comparison purposes only and are subject to change without notice. Specification(s) for your individual Bobcat equipment will vary based on normal variations in design, manufacturing, operating conditions, and other factors. Where applicable, dimensions are in accordance with ISO standards. Specifications and design are subject to change without notice. Pictures of Bobcat units may show other than standard equipment. All dimensions are given for mini track loaders. All dimensions are shown in inches. Respective metric dimensions are enclosed by parentheses. Bobcat Company complies with the requirements of ISO 9001 as registered with BSI.

Bobcat®, the Bobcat logo and the colors of the Bobcat machine are registered trademarks of Bobcat Company in the United States and various other countries. ©2021 Bobcat Company. All rights reserved.



Printed on 10% recycled paper

B-1998 (02/21)

Bobcat Company
250 East Beaton Drive • West Fargo, ND 58078

Bobcat.com



Bobcat®

One Tough Animal.